

PATENT  
450111-03686

## BEST AVAILABLE COPY

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application. An identifier indicating the status of each claim is provided.

Listing of Claims

1. (Currently Amended) A receiver for a communication system including a plurality of base stations and a plurality of receivers, each base station transmitting a respective CDMA signal including data intended for each of a set of one or more of the receivers, the data intended for each of the receivers being encoded in the CDMA signal using a respective spreading code for that receiver; ~~receiver,~~ the receiver including:

reception means for receiving a signal including CDMA signals;

~~one or more~~ a plurality of branch processing means, the reception means being capable of transmitting the received signal to ~~the or each~~ branch processing means, ~~the or each~~ branch processing means corresponding to a respective one of the base stations and arranged to modify the received signal by the operations of:

(i) data ~~equalisation~~ equalization, based on a respective filter using a respective set of weights; and

(ii) decoding the spreading code for the receiver;

decision means for using the an output of ~~the or each~~ branch processing means to generate an error signal and an estimate signal indicative of the data in the received signal intended for the receiver; and

adaptation means for modifying ~~the or each~~ the respective set of weights using the error signal.

PATENT  
450111-03686

2. (Original) A receiver according to claim 1 for use in a communications system in which the CDMA signal transmitted by each base station is encoded using a respective scrambling code for that base station, and said decoding uses the scrambling code of the corresponding base station.

3. (Currently Amended) A receiver according to claim 2, ~~wherein in which~~  
~~there are at least two said branch processing means;~~  
said decision means ~~combining~~ combines the outputs of the ~~at least two~~ plurality of  
branch processing means into a combined signal ~~to generate a combined signal, and using the~~  
~~combined signal to generate the error signal and the estimate of the data in the received signal~~  
~~intended for the receiver.~~

4. (Currently Amended) A receiver according to claim 3, adapted to receive CDMA signals with a processing gain of N;  
said reception means generating G measurements in each chip duration of the CDMA signal, where G is an integer;  
each of said set of weights consisting of  $G(2M+1)$  weights, where M is an integer;  
said combined signal being a sum over the branch processing means of the product  
[[of]]of:

(i) a vector derived from said spreading code for the receiver and the scrambling code of the corresponding base station;

PATENT  
450111-03686

- (ii) a data matrix composed of said measurements and having  $G(2M+1) \times N$  components; and
- (iii) the set of weights for ~~that the~~ respective branch processing means.

5. (Previously Presented) A receiver according to claim 3 in which the detection means is arranged to generate said error signal as the difference between said combined signal and a correction signal.

6. (Original) A receiver according to claim 5 in which said detection means includes a non-linear function unit for generating said correction signal from said combined signal using a non-linear function.

7. (Original) A receiver according to claim 5 in which the detection means includes a training sequence input for receiving a training sequence, and a switch for selectively deriving said correction signal as a signal input to said training sequence input or the output of the decision means.

8. (Currently Amended) A method of extracting data intended for a first user from one or more CDMA signals, each broadcast by a respective base station, ~~the or each~~ CDMA signal including data intended for the first user and data intended one or more other users, the data for each user being encoded using a respective spreading ~~[[code;]]code~~, the method including:

receiving a signal including the one or more CDMA signals;

PATENT  
450111-03686

transmitting the received signal along ~~one or more~~ a plurality of processing branches corresponding to different respective said base stations;

~~in the or each branch~~ modifying the received signal in each processing branch by the operations of:

(i) ~~data equalisation~~ equalization in respect of the corresponding base station, based on a respective set of weights; and

(ii) decoding, using the spreading code for the first user;  
using an output signal generated ~~generating from the outputs of the or each processing~~  
~~branch an output signal, and using the output signal to derive an error signal[[,]]~~ and an estimate  
signal indicative of the data in the received signal intended for the first user; and  
modifying said each respective set ~~sets of~~ weights using the error signal.

9. (Currently Amended) A method according to claim 8 ~~in which, wherein~~  
the CDMA signal transmitted by each base station is encoded using a respective scrambling code  
~~for that base station, and said decoding uses using the scrambling code of the corresponding base~~  
station.

10. (Currently Amended) A method according to claim 9, wherein-in which  
~~the received signal is transmitted along at least two of said processing branches;~~  
said decision means output signal comprises a combined signal generated by combining  
the outputs of the at least two plurality of processing branches to generate a combined signal, and  
using the combined signal to generate the error signal and the estimate of the data in the  
received signal intended for the receiver.

PATENT  
450111-03686

11. (Currently Amended) A method according to claim 10 ~~in which, wherein~~  
said CDMA signals have a processing gain of N;  
said step of receiving a signal includes generating G measurements in each chip duration  
of the CDMA signal, where G is an integer;  
each of said set of weights ~~consists of~~ comprises  $G(2M+1)$  weights, where M is an  
integer; and  
said combined signal is a sum over the processing branches of the product ~~of~~ of:  
(i) a vector derived from said spreading code for the first ~~user receiver~~ and the  
scrambling code of the corresponding base station;  
(ii) a data matrix composed of said measurements and having  $(G(2M+1) \times N)$   
components, and  
(iii) the set of weights for ~~that the~~ respective processing branch.

12. (Original) A method according to claim 10 in which said error signal is the  
difference between said combined signal and a correction signal.

13. (Original) A method according to claim 12 further including generating said  
correction signal from said combined signal using a non-linear function.

14. (Original) A method according to claim 12 further including deriving said  
correction signal as a selection from an input training sequence or the estimate signal.

PATENT  
450111-0368615. (Currently Amended) A communication system ~~including comprising:~~a plurality of base ~~stations~~ stations; anda plurality of receivers, each base station being arranged to transmit a respective CDMA signal including data intended for each of a set of ~~one two~~ or more of the receivers encoded using a respective spreading code for the respective ~~receiver~~ receiver, each receiver including:

reception means for receiving a signal including CDMA signals;

~~one or more~~ a plurality of branch processing means, the reception means transmitting the received signal to ~~the or~~ each branch processing means, ~~the or~~ each branch processing means corresponding to a respective one of the base stations and arranged to modify the received signal by the operations of:

- (i) data ~~equalisation~~ equalization, based on a respective set of weights; and
- (ii) decoding, using the spreading code for that receiver;

decision means for using an output of ~~the or~~ each branch processing means to derive an error signal and an estimate of the data in the received signal intended for ~~that~~ the respective receiver; andadaptation means for modifying said respective set ~~sets~~ of weights using the error signal.

16. (Canceled)

17. (Canceled)

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER: \_\_\_\_\_**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**